

# Καταγραφικά DVR



Όραμά μας η δική σας ασφάλεια!



		D6104C-V2	D7108CM-V2	D8016CH
Compatible with AHD 1080P, AHD 720P, Analog 960H/D1, IP 1080P				
AHD new technology 1080N (960x1080) Decoding & Recording, 1080P image quality while save 50% storage space				
VIDEO	OPERATION SYSTEM	LINUX		
	VIDEO SYSTEM	NTSC/PAL Switch Selectable		
	INPUT	BNC*4, 1.0Vp-p, 75ohm	BNC*8, 1.0Vp-p, 75ohm	BNC*16, 1.0Vp-p, 75ohm
	SPOT	N/A		
	HDMI OUTPUT	1 HDMI Output		
	VGA OUTPUT	1 VGA Output		
AUDIO	INPUT	4CH, RCA	N/A	2CH, RCA
	OUTPUT	1CH, RCA	N/A	1CH, RCA
	TALK BACK	YES	N/A	YES
CON-TROL	MOUSE	2*USB2.0		
STO-RAGE	BUILD IN INTERFACE	SATA *1 (1*HDD 6TB )		
DIS-PLAY	DIVISION	1, 4	1, 4, 9	1, 4, 9,16
	ZOOM	Preview & Playback Zoom Support		
RECORDING	COMPRESSION	H.264 Dual stream (High profile)		
	RECORDING MODE	Manual/Schedule/Motion Detection/Sensor		
	ENCODING ABILITY	"4*15fps@1080P 4*25fps@1080N"	"8*12fps@1080P 8*25fps@1080N"	"8*25fps@1080P 16*12fps@1080P 16*25fps@1080N"
	DECODING ABILITY	"4*15fps@1080P 4*25fps@1080N"	"8*12fps@1080P 8*25fps@1080N"	"8*25fps@1080P 16*12fps@1080P 16*25fps@1080N"
	RESOLUTION	Analog: 4* 1080P;4* 1080N; Hybrid: 2*1080P (Analog) + 2*1080P (Network); Network: 8*1080P; 8*960P; 4*3M	Analog: 8* 1080P; 8* 1080N Hybrid: 4*1080P (Analog) + 4*1080P (Network); Network: 8*1080P; 16*960P; 4*5M; 4*3M	Analog: 16*1080P; 8*1080P; 16*1080N Hybrid: 8*1080P (Analog) + 8*1080P (Network)
		QUALITY	Lowest, Lower, Low, High, Higher, Highest	
PLAYBACK	SYNC PLAYBACK	1, 4	1, 4	1, 4, 8
	SPEED	Normal, FF (1X, 2X, 3X, 4X), RF (1X, 2X, 3X, 4X), Slow (1X, 2X, 3X, 4X)		
	SEARCH METHOD	Event, Channels and Calendar		
COMMUNICATION	REMOTE ACCESS	IE (10.0 and below), Chrome, Firefox, ISS (Windows XP/WIN7/WIN8/WIN10), ISS MOBILE2 (IOS, Android) - <b>FREE SOFTWARE</b>		
	REMOTE OPERATION	Remote View, Remote Playback, Remote Setup		
	NETWORK SERVICE	TCP/IP, PPPoE, DDNS, FTP, NTP, UPNP, SMTP, RTSP, HTTP **** <b>FREE DDNS SERVICE****</b>		
	MOBILE DEVICE	iPhone, iPad, Android		
	WAN RJ45	10/100Mbit/s		
	3G EXTERNAL MODULE	YES via USB	N/A	YES via USB
	WIFI EXTERNAL MODULE	YES via USB	N/A	YES via USB
	GUI INTERFACE	Supported GUI 16 Bit True Color		
	PTZ PROTOCOL	PELCO-D, PELCO-P, etc 21 kinds of protocol		
BACKUP	INTERNAL	N/A		
	EXTERNAL	2*USB2.0 - USB Disk up to 32G (Kingston)		
	NETWORK	YES		
	FILE FORMAT	H264/AVI		
GENERAL	ALARM IN/OUT	N/A		
	RS-485	1		
	RS-232	N/A		
	UNIT DIMENSION(mm)	W260*D220*H48mm	W260*D220*H48mm	W260*D220*H48mm
	OPERATION TEMPERATURE	10°~40°		
	WORKING HUMIDITY	10% ~ 90%		
POWER CONSUMPTION	DC 12V,2A, <15W (Exclude HDD)			



		D5004HH	D6008HH	D7016HH
		Compatible with AHD 1080P, AHD 720P, Analog 960H/D1		
		AHD new technology 1080N (960x1080) Decoding & Recording, 1080P image quality while save 50% storage space		
	OPERATION SYSTEM	LINUX		
	VIDEO SYSTEM	NTSC/PAL Switch Selectable		
VIDEO	INPUT	BNC*4, 1.0Vp-p, 75ohm	BNC*8, 1.0Vp-p, 75ohm	BNC*16, 1.0Vp-p, 75ohm
	CVBS OUTPUT	1 CVBS Output		
	SPOT	N/A		
	HDMI OUTPUT	1 HDMI Output		
	VGA OUTPUT	1 VGA Output		
AUDIO	INPUT	4CH, RCA	4CH, RCA	2CH, RCA
	OUTPUT	1CH, RCA	1CH, RCA	1CH, RCA
	TALK BACK	YES	YES	YES
CON- TROL	MOUSE	2*USB2.0		
	IR CONTROLLER	YES		
STO- RAGE	BUILD IN INTERFACE	SATA *1(1*HDD 4TB)		
DIS- PLAY	DIVISION	1, 4	1, 4	1, 4, 9,16
	ZOOM	Preview & Playback Zoom Support		
RECORDING	COMPRESSION	H.264 Dual stream (High profile)		
	RECORDING MODE	Manual/Schedule/Motion Detection/Sensor (Optional)		
	ENCODING ABILITY	PAL: 4*25fps@1080N/720P	PAL: 8*15fps@1080N/720P	PAL: 16*12fps@1080N/720P
	DECODING ABILITY	PAL: 4*25fps@1080N/720P	PAL: 4*15fps@1080N/720P	PAL: 16*12fps@1080N/720P
	RESOLUTION	Analog: 4*1080N	Analog: 8*1080N	Analog: 16*1080N
		Hybird: 2*1080N (Analog) + 2*1080P (Network)	Hybird: 4*1080N (Analog) + 4*720P (Network)	Hybird: 8*1080N (Analog) + 8*960P (Network)
QUALITY	Network: 4*1080P;	Network: 8*720P;	Network: 8*1080P; 16*960P; 4*3M; 4*5M	
PLAYBACK	SYNC PLAYBACK	1, 4	1, 4	1, 4, 8, 16
	SPEED	Normal, FF(1X, 2X, 4X, 8X,), Slow (1/2X, 1/4X, 1/8X)		
	SEARCH METHOD	Time, Event, Channels and Calendar		
COMMUNICATION	REMOTE ACCESS	IE (10.0 and below), ISS (Windows XP/WIN7/WIN8/WIN10), ISS MOBILE2 (IOS, Android) - <b>FREE SOFTWARE</b>		
	REMOTE OPERATION	Remote View, Remote Playback, Remote Setup		
	NETWORK SERVICE	TCP/IP, PPPOE, DDNS, FTP, NTP UPNP **** <b>FREE DDNS SERVICE****</b>		
	MOBILE DEVICE	iPhone, iPad, Android		
	WAN RJ45	10/100Mbit/s		
	3G EXTERNAL MODULE	N/A		
	WIFI EXTERNAL MODULE	N/A		
	GUI INTERFACE	Supported GUI 16 Bit True Color		
	PTZ PROTOCOL	PELCO-D, PELCO-P, etc 17 kinds of protocol		
BACKUP	INTERNAL	N/A		
	EXTERNAL	2*USB2.0 - USB Disk up to 32G (Kingston)		
	NETWORK	YES		
	FILE FORMAT	AVI		
GENERAL	ALARM IN/OUT	N/A		
	RS-485	1		
	RS-232	N/A		
	UNIT DIMENSION(mm)	260(L) x 44(H) x 221(W)	260(L) x 44(H) x 221(W)	260(L) x 44(H) x 221(W)
	OPERATION TEMPERATURE	10°~ 40°		
	WORKING HUMIDITY	10% ~ 90%		
POWER CONSUMPTION	DC 12V, 2A, <6W (Exclude HDD)	DC 12V, 2A, <6W (Exclude HDD)	DC 12V, 2A, <13W (Exclude HDD)	



	D5004AH	D6008AHM	D7016CH
Compatible with AHD 1080P, AHD 720P, Analog 960H/D1			
AHD new technology 1080N(960x1080) Decoding & Recording, 1080P image quality while save 50% storage space			
OPERATION SYSTEM	LINUX		
VIDEO SYSTEM	NTSC/PAL Switch Selectable		
INPUT	BNC*4, 1.0Vp-p, 75ohm	BNC*8, 1.0Vp-p, 75ohm	BNC*16, 1.0Vp-p, 75ohm
CVBS OUTPUT	1 CVBS Output		
SPOT	N/A		
HDMI OUTPUT	1 HDMI Output		
VGA OUTPUT	1 VGA Output		
INPUT	4CH, RCA	4CH, RCA	NA
OUTPUT	1CH, RCA	1CH, RCA	NA
TALK BACK	YES	YES	NA
MOUSE	2*USB2.0		
IR CONTROLLER	YES		
BUILD IN INTERFACE	SATA *1(1*HDD 4TB)		
DIVISION	1, 4	1, 4, 9	1, 4, 9, 16
ZOOM	Preview & Playback Zoom Support		
COMPRESSION	H.264 Dual stream (High profile)		
RECORDING MODE	Manual / Schedule / Motion Detection / Sensor (Optional)		
ENCODING ABILITY	PAL: 4*25fps@1080N/720P	PAL: 8*15fps@1080N/720P	PAL: 16*25fps@1080N/720P
DECODING ABILITY	PAL: 4*25fps@1080N/720P	PAL: 8*15fps@1080N/720P	PAL: 16*25fps@1080N/720P
RESOLUTION	Analog 4*1080N	Analog 8*1080N	Analog 16*1080N
	Hybird 2*1080N (Analog) + 2*1080P (Network)	Hybird 4*1080N (Analog) + 4*720P (Network)	Hybird 8*1080N (Analog) + 8*720P (Network)
	Network 4*1080P;	Network 8*720P;	Network: 8*1080P; 16*960P; 4*3M; 4*5M
QUALITY	Worst, Worse, Bad, Normal, Better, Best		
SYNC PLAYBACK	1, 4		
SPEED	Normal, FF (1X, 2X, 4X, 8X), Slow (1/2X, 1/4X, 1/8X)		
SEARCH METHOD	Time, Event, Channels and Calendar		
REMOTE ACCESS	IE (10.0 and below), ISS (Windows XP/WIN7/WIN8/WIN10), ISS MOBILE2 (IOS, Android) - <b>FREE SOFTWARE</b>		
REMOTE OPERATION	Remote View, Remote Playback, Remote Setup		
NETWORK SERVICE	TCP/IP, PPPOE, DDNS, FTP, NTP UPNP **** <b>FREE DDNS SERVICE****</b>		
MOBILE DEVICE	iPhone, iPad, Android		
WAN RJ45	10/100Mbit/s		
3G EXTERNAL MODULE	Yes, with USB 2.0 Port (Optional)		
WIFI EXTERNAL MODULE	Yes, with USB 2.0 Port, 100 Meters (Optional)		
GUI INTERFACE	Supported GUI 16 Bit True Color		
PTZ PROTOCOL	PELCO-D, PELCO-P, etc 17 kinds of protocol		
INTERNAL	N/A		
EXTERNAL	2*USB2.0 - USB Disk up to 32G(Kingston)		
NETWORK	YES		
FILE FORMAT	AVI		
ALARM IN/OUT	N/A	4 Alarm Input, 1 Alarm Output	N/A
RS-485	1		
RS-232	N/A		
UNIT DIMENSION(mm)	260(L) x 44(H) x 221(W)	260(L) x 44(H) x 221(W)	260(L) x 44(H) x 221(W)
OPERATION TEMPERATURE	10° ~ 40°		
WORKING HUMIDITY	10% ~ 90%		
POWER CONSUMPTION	DC 12V, 2A, <6W (Exclude HDD)	DC 12V, 2A, <6W (Exclude HDD)	DC 12V, 2A, <13W (Exclude HDD)

