VISION-XIP Product Matrix

Showing Products Scheduled For Release In 2023 - Firmware Release V3.00.69 ENG

Any one of the IP modules shown on the right can be installed. IP via Wi-Fi is available when the Wi-Fi enabled keypad is used.

P/N - MY746AU
Plug On 4G GSM/ GPRS Module

or

P/N - MY368AU
IP Communications Module 4G GSM/GPRS/Ethernet

or

P/N - CM751
Plug On Ethernet IP Module

P/N - SW500
VisionLink (Licence Key)
Upload/Download Software
For Installers

x1

P/N - CC714P
Vision-XIP Security Controller PCB

P/N - CM195
Multi RF Receiver Interface

x1

x3

RFRC-STR2

P/N - SW501
Site Manager (Licence Key)
Onsite Administration Software
(IP Ethernet Connectivity Required)

Panel supports direct RFRC-STR2 serial connection or via CM195

RFRP2 Wireless transceiver- Repeater F.01.U.389.906
Note: Repeater is not compatible with 2 Way SMART RF

RFRC-STR2
RF Receiver Directly Connected

x1

P/N - CM710
4 Way LAN Relay Output Expander Module

x8

P/N - CM720
1 Amp LAN Power Supply & Battery Charger Module

x8

P/N - CM760
Real Time Clock Module

x1

SMART DEVICE APPS

Smart device apps are available to enhance alarm reporting and provide real time control of system areas, outputs and doors etc. More information can be found in the app stores, or on the MyAlarm web site at www.myalarm.com.au.

iFob Control

SMS Control

MyAlarm

P/N - RF120
SMART RF LAN Base Station Receiver 2-Way

x4

P/N - RF110
SMART RF - 5 Button 2-Way Keyfob IP67

P/N - RF110FK
Colour Fascia Kit To Suit RF110 Keyfobs

P/N - RF121
SMART RF LAN Base Station Receiver With 4 Relay Outputs 2-Way

P/N - RF112
SMART RF Reed-HW Input+Shock+Pulse

P/N - RF113
SMART RF SM Reed-HW Input+PWR Out

P/N - RF160
SMART RF 2 Channel Wireless Output Module

SMARTRF

bit.ly/SmartRF

Up to 16 keypad devices of any type can be installed on the Vision-X panel. This includes Keypads, Readers and Weigand to LAN Interfaces.

SMART CARD CREDENTIALS AND LAN READERS

P/N - PR365
Adhesive Smart Card Sticker

P/N - PR350
ISO Smart Card

P/N - PR301
Smart Card Token

P/N - PR370
Dual Smart Card and EM Format Token

Light Switch Style
LAN S/C Reader
P/N - PR120 White
P/N - PR121 Black

3.5" Colour Keypad with Internal Smart Card Reader
P/N - CP736 White

External Smart Card Reader
P/N - PR116 White
P/N - PR115 Black

Internal Smart Card Reader
P/N - PR114 White
P/N - PR113 Black

P/N - CP156
Slim Style External Metal Keypad with Smart Card Reader

P/N - CP155
External Keypad with Smart Card Reader

WiFi

3.5" Colour Keypad With S/C + Wi-Fi + Tamper
P/N - CP737 White

VISION-XIP Product Matrix

Showing Products Scheduled For Release In 2023 - Firmware Release V3.00.69 ENG

P/N - CP799
Service Keypad Installer Tool

P/N - CM797
LAN Isolator Module

x8

Up to 8 LAN Isolator modules can be connected Isolators provide electrical isolation between LAN segments reducing the chance of surge damage. Isolators can also be used to increase the total LAN length beyond 1200m.

P/N - CM704
8/16 LAN Zone Expander

x8

Up to 8 zone expanders of any type can be connected to the system. When using Single or Alarm & Tamper EOL, the CM707 can be installed to provide 16 zones on the CM705 Expander. The CM707 cannot be installed when using split EOL monitoring.

Maximum panel zone count configuration is:
Single EOL = 136
Alarm & Tamper =136
Split EOL = 144

P/N - CM707
8 Zone Piggy Back Expander

x8

P/N - CM705
8/16 Universal LAN Zone Expander with Cabinet

P/N - CM705P
8/16 Universal LAN Zone Expander PWA Only

P/N - CM430S
LAN to Ethernet Converter Module

P/N - CM796
Weigand to RS485 LAN Interface Module

x15

= Encrypted RS485 LAN
= ISOLATED Encrypted RS485 LAN
= Programmable Serial Input
= TCP/IP Network Link
= Encrypted RS485 LAN 2

Weigand to LAN Interface can support 3rd party readers up to 40 bits.

P/N - PR100
External Weigand Reader (Not Smart Card Compatible)

The CM723 and CM724 can be easily installed inside the CM350, MW720 and MW730 enclosures.

P/N - CM723
5 Amp LAN P/S Module With Dual Battery Chargers

P/N - CM724
5 Amp LAN P/S Module With Dual Battery Chargers Export Model

3 YEAR WARRANTY

Some features and modules types may require panel and or module firmware updates to operate. Please see individual product documentation for minimum requirements.

Made In Australia

P/N - CM910
Combined Direct Link \ Flash Programmer Interface - USB

P/N - CM444
Slim Style Relay Card Form C - 2 Amp

P/N - CM435
Power Terminal Expander Module

P/N - CM940
6 Way Programmable Relay Card. Can be separated into single relays.

P/N - CM255
Panel Default Unlock Key Will reset Installer PIN and RAS PIN on Vision-X panels.

P/N - CM436
Desktop Reader Interface For 3rd party Weigand Readers. No Reader supplied.

P/N - CM438
USB powered Desktop Reader Interface for DF format EM Prox tokens.

P/N - CM439
USB powered Desktop Reader Interface for DF MiFare Smart Card tokens.

Desktop readers are for use with Solutionlink and Site Manager Software packages and allow user credentials to be learnt at the PC.

Copyright © 2023 Digiflex — In the interest of ongoing product improvement we reserve the right to change specifications at any time without notice — E&OE — Vision-X Product Matrix 6/2023

Copyright © 2023 Digiflex — In the interest of ongoing product improvement we reserve the right to change specifications at any time without notice — E&OE — Vision-X Product Matrix 6/2023

ΟΡΑΜΑ ΜΑΣ Η ΔΙΚΗ ΣΑΣ ΑΣΦΑΛΕΙΑ ™

ΔΙΑΓΡΑΜΜΑ ΣΥΣΤΗΜΑΤΟΣ