SOYAL®

Comparison Table of SOYAL Relay

Product / Functions & Features	AR-721RB	AR-821RB	AR-829RB	Controller Home Series(H Series)/ Enterprise Series(E Series)
				
Positive Trigger Contact	✓	✗	✓	
Low Trigger Contact	✓	✓	✓	
Frequency	DI1	✗	✗	
Voltage	12VDC	12VDC	12VDC	
Power Consumption	40mA	20mA/40mA	40mA	
Output Contact	1 Form C, 12A at 125VAC, 7A at 250VAC, 7A at 30VDC	1 Form C, 12A at 125VAC, 7A at 250VAC, 7A at 30VDC	2 Form C 1A at 120VAC, 2A at 24VDC	
Operating Temperature	-20°C ~ +70°C	-20°C to +70°C	-20°C to +70°C	
Dimension(mm)	33.6(H)X47.8(W)X22.6(D)	20(H)X32(W)X29(D)	55(H)X25(W)X17.5(D)	
N.W. (g)	approx.40	approx.20	approx.30	
Delay time by DIP switch (determined by the distance between push button and the door.)	0.1,3,6,9 sec.	✗	✗	
Support the digital opening signal to enhance the security	✓	✗	✗	
Enable Auto Relock	✗	✗	✗	✓